


SXR7000: SEVEN TONNE ROTARY TIPPING DUMPER
Capacities:

Payload capacity – tonnes	7
Liquid capacity – ltr	1920
Struck capacity – ltr	2502
Heaped capacity – ltr	3457

Dimensions:

A = overall length – mm	4579
B = overall height - ROPS up – mm	3160
C = overall height - ROPS down – mm	2130
D = overall height - skip tipped – mm	3583
E = prow height – mm	1685
F = tipped prow height – mm	1080
G = side loading height – mm	1880
H = wheel base – mm	2400
I = ground clearance – mm	320
Overall width – mm	2321
Width over tyres – mm	2280
Outer turning circle – metres	12.5

Weight:

Unladen weight – kg (with ROPS and full tanks)	4800
--	------

Engine type:

Iveco N45MSSX00 74kW @ 2300rpm	4485cc
--------------------------------	--------

Transmission:

Powershuttle transmission, 4 speeds forward and reverse with torque converter. Heavy duty drive train.

Axles and brakes:

Heavy duty double reduction axles with totally enclosed oil immersed disc brake. Transmission parking brake (front only)

Wheels and tyres:

405/70 - 20	14 ply
-------------	--------

Tank capacities:

68 ltr fuel tank	40 ltr hydraulic tank
------------------	-----------------------

Road speed mph/kph:

1st gear:	3.0	4.8
2nd gear:	4.9	7.8
3rd gear:	9.2	14.7
4th gear:	16.7	26.8