



Model 601 Hydrostatic Articulating Grader



Overall Dimensions:

Length: 16'9"
Width: 5'8"
Height: 7'6"

Weight:

6400 lbs.

Moldboard:

Size: 8' wide X 16" high
Clearance: 13"
Cut Depth: 5"
Tilt: 40°
Blade Angle: 40° left or right from center
Blade Type: 1/2" X 6" X 8' reversible

Dozer Blade:

Size: 6' wide X 14" high
Clearance: 11"
Cut depth: 4"
Blade Type: 1/2" X 6" X 6' reversible

Scarifier:

4 teeth, 24" rip width
replaceable tips

Steering:

40° front wheel power steering
Articulates 20° left or right from center

Tire Size:

10-16.5 10 ply rating
Optional 12-16.5 10 ply rating

Drive System:

4 wheel hydrostatic drive
Travel speed 0-3.5 low/ 0-8 high

Engine:

49.5 hp Kubota water-cooled
4 cylinder diesel engine

Fluid Capacities:

Fuel: 12 US gallons
Hydraulic: 14 US gallons



Optional Loader System:

Lift Height: 9'6"
Will load tandem axle dump
Universal Quick-Attach Tool Bar
(will accept other skid steer attachments;
i.e. bucket, sweeper, forks)
Auxiliary implement circuit for attachments
Max Flow Rate 12 GPM

Manufactured By:

Shannon Chastain Enterprises, Inc.
185 Harmony Rd. Eatonton, GA 31024
(706) 484-2253

www.basicequipment.net

Shannon Chastain Enterprises, Inc. reserves the right to change specifications without notice in an effort to improve product quality.

Courtesy of Machine.Market