Bergmann Dumper 2030 hi swivel



Strong arguments for your advantage

- high stability thanks to oscillating axle
- ► hydraulical park brake
- instrument board lowerable and lockable
- type test approval by TBG

Advantages of Bergmann dumper:

- > TÜV and TBG approvals
- Movable parts made from chrome
- Wide tyres for all models
- > Hydraulic park brakes
- Ergonomic operator's stand
- Easy access to all maintanance and service points
- > Lowerable and lockable instrument board
- > Articulated steering / oscillating rear axle



Bergmann Dumper 2030 hi swivel

Technical Data

Weight/ bucket capacity	Payload		2.500 kg	
, ,	Unladen weight		2.340 kg	
	Struck level			1.150 L
	Heaped		1,8 m ³	
			hydraulical	ly swivelling and tipping
	·		bucket by 180°	
			,	
Dimensions	Total height with protection bar			2.780 mm
	Total height without protection bar			1.990 mm
	Total length			3.940 mm
	Total width			1.780 mm
	Tipping height			1.150 – 1.850 mm
	Ground clearance			246 mm
Transmission	Hydrostatic 4-wheel-drive			
	speed I:	0-10 km/h		
	speed II:	0-23 km/h		
Steering	Hydraulic articulated steering acting over priority flow			
	Steering angle 40° to each side			
	3 3			
Axles / Brakes	Front axle rigid, rear axle oscillating stored +/- 12°, maintenance-free-oil-			
	bath multi-disc brake with automatic adjustment in the front axle, hydraulically applicated locking brake acting over articulated shaft on front and rear axle.			
Engine	3 cylinder Kubota Diesel engine –water cooled-			
	Output power 25,5 KW at 2.800 rpm.			
-	C	15 15 16 B ("I		
Tyres	Standard, 11,5/80-15.3 AS Profil			
T 1 2	F 1501			
Tank capacity	Fuel 50 L			
	Hydraulic oil 40 L			
Floatrica	10\/ alaatriaal inst	والمعالمة والمالية	مامخاند	ral panal for anaina
Electrics	12V electrical installation with main switch, control panel for engine			
	water temperature, fuel and service hour meter, control lamps for motor			
	oil; park brake, direction indicator, battery charging control, hydraulic filter, display for drive position			
	miler, display 101 (arive position		
Standard Equipment	Hydro sprung sea	t adjustable and col	lansible inst	trument panel lowerable
Standard Equipment	Hydro sprung seat adjustable and collapsible, instrument panel lowerable and lockable with ignition key, tow-bar coupling, lighting system			
	according to German traffic regulations, bucket from abrasion-proof fine grain steel, EC type test approval, EC declaration of conformity, operator's manual /			
	spare parts list			