



PTB - 202, 302

FEATURES

- Variable GVWR Range
- Variable Payload Range
- Variable Length Adjustments
- Cargo Bed Between Center and Rear Bolsters
- Tubular Construction
- 6-Position Adjustable Hitch
- Multiple Axle Capacities
- Multiple Stanchion Configurations
- Internal Electric and/or Air Lines (No Coil Cords)
- Tandem Axle Dual Wheels
- 4" W Ratchet Pole Straps with Winch Binders at each Bolster

OPTIONS

- Air Brake Upgrade
- Galvanized Finish Upgrade
- Optional Pole Mounted Light Bar
- · Optional Tool Boxes
- Bedliner in Cargo Floor
- Rear Pull Out Upgrade
- 5th Wheel Semi Upgrade

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

SPECIFICATIONS

GVWR Range	23,500 - 50,000 lbs
Payload Range	17,700 - 40,000 lbs
Axle Manufacturer	Dexter
Axle Size	10,000 - 20,000 lbs
Tires	235 / 80R16, 215 / 75R17.5, 255 / 70R22.5
Wheels	16" x 6" , 17.5" x 6.75", 22.5 Duals
Overall Width	95"
Jack	12,000 lb Drop Leg
Overall Length Retracted (202)	40.5'
Overall Length Extended (302)	74'
Bolster Width	95"
Hitch	2 1/2" or 3" Lunette Eye
Bolster Height	44"
Construction	Tubular

PTB - 202 WITH 5TH WHEEL UPGRADE



PTB - 302



GALVANIZED FINISH UPGRADE



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

