



Series:

RAFS

Bottomless Finishing Scraper

For use with tractors in the 200 – 400hp range.



FEATURES:

- Capable of utilizing a single or dual mast machine control system.
- Excellent for all leveling applications.
- Smooth and maintain access roads or haul roads.
- Rework washed out terraces.
- Rigid construction insures leveling accuracy.
- Up to 3" (102mm) cutting depth.
- Reversible and replaceable side cutter blades.
- Offset walking beam transport unit provides stability at higher operating speeds.
- Rear operating axle can be split to walk contours.



Scan the code to visit our website today:
www.romeplow.com



Specifications:

Series RAFS Bottomless Finishing Scraper

Model Number	Capacity yd ³ (m ³)	Overall Dimensions			Suggested Engine Hp		Net Weight lbs (kg)
		Length ft/in (m)	Width ft/in (m)	Height ft/in (m)	4 Mph	6 Mph	
RAFS-20	11.9 (8.4)	20'-10" (6.4)	20'-0" (6.1)	4'-6" (1.4)	200	250	11,225 (5092)
RAFS-24	14.3 (11)	20'-10" (6.4)	24'-0" (7.3)	4'-6" (1.4)	250	300	12,125 (5500)

* Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. One rear tractor hydraulic circuits required for scraper operation.

Standard Equipment:

- Laser or GPS receiver platforms.
- Breakaway front tongue.
- Four 21.5 x 16.1 tires on the operating transport.
- Adjustable front hitch clevis height.
- Reversible and replaceable cutting edges and side cutter blades.
- Drawbar jack and safety chain.

Optional Equipment:

- Laser valve group (without laser).
- Light group.



Rome Plow
 475 Sixth Street
 P.O. Box 48
 Cedartown, GA 30125, USA

Telephone: 770.748.4450
 Fax: 770.748.4427
 Website: romeplow.com