SP 575 Dual Spray/Squeegee Machine





Standard Features:

• 14 gallon water tank on each side.



User-Friendly Control Panel

Power

Steering



Rear Wheel Direct-Drive



Hydraulically Driven Dual Diaphragm Material Pump



Hydraulic Shift Option for Angling the Squeegee



Dual Easy-Open Butterfly Sealer Discharge Valves

The SP 575 Dual is a 575 gallon spray/squeegee machine designed to mix and apply pavement sealers with or without

SP 575 Features:

- Round tank design with true full sweep agitation and rubber wiper blades.
- SandPumper II material pump-shifts to neutral when wand or spray bar is shut off. 75 GPM output.
- Floating squeegee assembly with rear angling squeegee (windrow features) and front box squeegee.
- ALL WHEEL DRIVE for added traction and easier trailer loading.
- Water fog system with electric water pump for fogging pavement.
- Spray bar, spray wand.
- Power steering for ease of maneuvering.
- Easy open butterfly sealer discharge valves.
- Emergency brake.

SP 575 Dual:

51 575 Duui.				
	PRODUCT #	DESCRIPTION	WT.	
	E1005	SP 575 Dual	4,760 lbs.	
	E9000	Blocking/Bracing Charge	400 lbs.	

*Call for pricing

Specifications:

Specifications:	
• Height	74"
• Width	
• Length	14′
Wheel Base	
Squeegee Width	104"
• Weight	4,760 lbs.
Material Tank Capacity	
Water Tank Capacity	28 gallons
Fngine	42 H.P. Kubota