



Reliable Construction Equipment — Since 1965

T5C | Compact Tractor Loader Backhoe



T5C Compact Tractor Loader Backhoe (CTLB)

Terramite's T5C is compact enough to fit in many areas inaccessible to larger machines. It is a rugged machine and has the power to tackle many of the "big machine jobs", such as septic tank installations, water, sewer and gas lines, landscaping, spreading or loading.

This T5C model CTLB is a profit-making and money saving machine! The T5C is used daily by utility companies, rental centers, contractors, plumbers, cemeteries, municipalities, golf courses, and more.

Terramite is the original manufacturer of compact tractor loader backhoes.
If you want quality—you want Terramite.

Specification Highlights

- 20 HP Gasoline
- 8' 4" Dig Depth
- 1700 lb Loader Lift Capacity
- 5900 lb Backhoe Break-out Force
- 3180 lbs Weight

Key Benefits

- Rigid Frame
- All Steel Construction
- Low Maintenance Costs
- Made in America

Terramite
600 Goff Mountain Road
Charleston, WV 25313 USA

(800) 428-3772
(304) 776-4231
(304) 776-4845 fax

www.terramite.com
sales@terramite.com

Terramite Representation Worldwide: United States | Puerto Rico | Canada | South America | South Africa | China

Courtesy of Machine.Market

SPECIFICATIONS

T5C

Compact Tractor
Loader Backhoe

STANDARD ENGINE: Kohler Command 20 HP Gasoline

LUBRICATION: Pressurized Filter

TRANSMISSION: Heavy Duty Hydrastatic

DRIVE MOTOR: Heavy Duty Gerotor

FRONT AXLE:

Construction Heavy Duty 1" x 5" Crossbeam
Spindle Size 1¾" Diameter
Steering Hydraulic Power

REAR AXLE:

Style Rigid Drive Axle, Limited Slip
Ratio 4.88 : 1

TIRES:

Front 20.5" x 8" x 10" 4 Ply (Optional 23" x 8.5" x 12" Skid Steer)
Rear 9.5" x 16" 6 Ply
Optional 31" x 15.5" x 15" High Flotation

CAPACITIES:

Fuel Tank U.S.- 9.5 Gallons Metric- 36 Liters Hydraulic Tank U.S.- 9.5 Gallons Metric- 36 Liters

HYDRAULIC SYSTEM FOR BACKHOE & ENDLOADER:

Pump	Flow	Pressure		Loader Valve	Backhoe Valve	Cylinders
Gear Type	7 GPM at 3600 RPM	U.S. 2400 P.S.I.	Metric 144 bar	2 Spool Monoblock	6 Spool Stack Type	2", 2½"

MEASUREMENTS:

	U.S.	Metric		U.S.	Metric
Loader Dump Height	81 inches	206 cm	Wheelbase	58 inches	147 cm
Digging Depth	100 inches	254 cm	Overall Width	48 inches	122 cm
Backhoe Reach	132 inches	335 cm	Overall Height	82 inches	208 cm
Rear Bucket Dump Height	80 inches	203 cm	Transport Length	156 inches	396 cm
Front Tire to Front Bucket	51 inches	130 cm	Transport Weight	3180 lbs.	1443 kg

CAPACITIES & FORCES:

Calculated SAE Dig Forces			Buckets		Capacity	
	U.S.	Metric	U.S.	Metric	U.S.	Metric
Dipstick	2800 lbs.	1270 kg	8"	203 mm	.90 cu. ft.	26 cu.dm
Bucket Curl	3100 lbs.	1406 kg	12"	305 mm	1.35 cu. ft.	38 cu.dm
Backhoe Lift	750 lbs.	340 kg	16"	406 mm	1.80 cu. ft.	51 cu.dm
Front Curl	2200 lbs.	998 kg	20"	508 mm	2.20 cu. ft.	62 cu.dm
Loader Lift	1700 lbs.	771 kg	24"	610 mm	2.40 cu. ft.	68 cu.dm
			36"	914 mm	3.10 cu. ft.	88 cu.dm

LOADER CAPACITY: Standard U.S. - 1/4 Yard

Metric - 0.210 m³

REAR BUCKET ROTATION: 180 Degrees

FRONT BUCKET ROLLBACK: 35 Degrees

REAR BOOM SWING: 135 Degrees

OPTIONAL EQUIPMENT:

Strobe Lights
Work Lights
Canopy
Rear Hydraulics

Specifications are subject to change without notice.

terramite®

Reliable Construction Equipment — Since 1965

Terramite
600 Goff Mountain Road
Charleston, WV 25313 USA

(800) 428-3772
(304) 776-4231
(304) 776-4845 fax

www.terramite.com
sales@terramite.com

Terramite Representation Worldwide: United States | Puerto Rico | Canada | South America | South Africa | China

Courtesy of Machine.Market