

































# Standard equipment

16  
17

	W 150 CF	W 150 CFi
<b>Base machine</b>		
Basic machine with engine	■	■
Machine chassis with wasp waist on the right side (zero edge)	■	■
Electrohydraulically opening engine cover	■	■
Radiator with temperature-dependent fan speed	■	■
Additional operating switches for lower scraper on the right	■	■
Elastically mounted engine station with low vibration and low noise	■	■
Three milling drum rotation speeds with electric on/off function 127 r.p.m. - 109 r.p.m. - 97 r.p.m.	■	■
Air compressor system	■	■
Exhaust post-treatment diesel oxidation catalyst DOC	—	□
<b>Milling drum unit</b>		
The right side of the milling drum housing can easily be folded down for maintenance or milling drum change	■	■
Hydraulic material depressor with conveyor lifting function	■	■
Hydraulically opening scraper plate with convenience locking	■	■
Exchangeable wearing segments on the side plate	■	■
Milling drum housing FB1500	□	□
<b>Milling drums</b>		
Milling drum FB1500 HT22 LA15 with 136 picks	□	□
<b>Milled-out material loading</b>		
Discharge conveyor slewing angle left 60 degrees - right 60 degrees	■	■
Discharge conveyor with adjustable conveyor speed and 2 slewing speeds for precise loading	■	■
Machine with hydraulic standard coupling for the discharge conveyor	□	□
Discharge conveyor, 8,150 mm long, 600 mm wide, without folding device	□	□
<b>Machine control and levelling system</b>		
Load-dependent advance control	■	■
4-track drive with manually activated, electronic anti-slip control	■	■
4 selectable steering modes	■	■
Automatic engine speed control	■	■
<b>Operator's stand</b>		
Convenient operating panel with practical switches	■	■
Multi-function armrest including colour operating display for one-handed operation of most machine functions	■	■

- = Standard equipment
- = Standard equipment, replaceable with optional equipment
- = Optional equipment



	W 150 CF	W 150 CFi
<b>Operator's stand</b>		
Digital multi-function display for all important operating conditions	■	■
Operating panel nighttime lighting	■	■
Robust anti-vandalism protection for the controls	■	■
Adjustable steering wheel position	■	■
Optimally positionable operator's seat	■	■
Footstep right and left with conveniently folding ladder	■	■
Two mirrors front, one mirror middle and one mirror in rear area of the machine	■	■
Standard operator's seat	□	□
<b>Under-carriage and height adjustment</b>		
LEVEL PRO PLUS levelling system. Measurement by travel measuring sensors in the side plate cylinder. The milling depth is displayed and set intuitively on the LEVEL PRO PLUS operating display. Including preliminary equipment for additional sensors.	■	■
Jog mode for height adjustment	■	■
High machine stability due to quadruple pendulum axle	■	■
PTS - machine automatically guided parallel with the road surface	■	■
ISC - intelligent track speed control with hydraulic four chain drive	■	■
Scraper height is shown on the display	■	■
Reversing with the drum rotating; simple and fast manoeuvring	■	■
Equipped with extremely wear-resistant 2-piece polyurethane track pads	■	■
<b>Others</b>		
Automatic water management	■	■
Large tool package	■	■
Generously sized water and diesel tanks	■	■
Total of 3 EMERGENCY STOP switches at sensible positions on the machine	■	■
Machine preparation for installing the control unit for WITOS FleetView	—	■
"Welcome" and "Go home" lights feature including LED lighting in the area of the operator's access and platform	■	■
European type test certificate and CE conformity	■	■
Paint standard cream white RAL 9001	□	□
Halogen/LED lighting package including rotating beacon	□	□
Electrohydraulic unit	□	□

■ = Standard equipment  
 ■ = Standard equipment, replaceable with optional equipment  
 □ = Optional equipment

# Optional equipment

18  
19

	W 150 CF	W 150 CFi
<b>Base machine</b>		
Exhaust post-treatment diesel oxidation catalyst DOC with diesel particulate filter DPF	—	<input type="checkbox"/>
<b>Milling drum unit</b>		
Milling drum housing FB1500 FCS-L	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum housing FB1500 FCS	<input type="checkbox"/>	<input type="checkbox"/>
Overload sensor on the scraper	<input type="checkbox"/>	<input type="checkbox"/>
Active floating position for the right and left side plates	<input type="checkbox"/>	<input type="checkbox"/>
<b>Milling drums</b>		
Milling drum FB1500 HT22 LA15 FCS with 136 picks	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum FB1500 HT22 LA18 FCS with 120 picks	<input type="checkbox"/>	<input type="checkbox"/>
FCS milling unit FB600 HT22	<input type="checkbox"/>	<input type="checkbox"/>
FCS milling unit FB900 HT22	<input type="checkbox"/>	<input type="checkbox"/>
FCS milling unit FB1200 HT22	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum FB1500 HT22 LA8 FCS with 210 picks	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum FB1500 HT5 LA6X2 FCS with 512 picks	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum FB1500 HT22 LA25 FCS with 102 picks	<input type="checkbox"/>	<input type="checkbox"/>
<b>Milled-out material loading</b>		
Machine with hydraulic quick-change coupling for the discharge conveyor	<input type="checkbox"/>	<input type="checkbox"/>
Discharge conveyor, 8,150 mm long, 600 mm wide, with hydraulic folding device	<input type="checkbox"/>	<input type="checkbox"/>
Shortened discharge conveyor, 7,250 mm long, 600 mm wide, with hydraulic folding device	<input type="checkbox"/>	<input type="checkbox"/>
VCS extraction system	<input type="checkbox"/>	<input type="checkbox"/>
<b>Machine control and levelling system</b>		
Increased travelling speed (up to 7.5 km/h)	<input type="checkbox"/>	<input type="checkbox"/>
Precision steering by pushbuttons	<input type="checkbox"/>	<input type="checkbox"/>
Sonic-Ski sensor for scanning in front of the milling drum right or left	<input type="checkbox"/>	<input type="checkbox"/>
Levelling boom for scanning up to 4 m to the side of the machine	<input type="checkbox"/>	<input type="checkbox"/>
Scanning in front of the milling drum unit	<input type="checkbox"/>	<input type="checkbox"/>
Operating display LEVEL PRO PLUS additionally	<input type="checkbox"/>	<input type="checkbox"/>
Multiplex preliminary equipment comprising 4 sensor sockets and holders	<input type="checkbox"/>	<input type="checkbox"/>
Multiplex 3-way right with 2 ultrasonic sensors	<input type="checkbox"/>	<input type="checkbox"/>
Multiplex 3-way right + left with 4 ultrasonic sensors	<input type="checkbox"/>	<input type="checkbox"/>
Level control 3D levelling pre-equipment	<input type="checkbox"/>	<input type="checkbox"/>
Basic equipment laser levelling without laser transmitter	<input type="checkbox"/>	<input type="checkbox"/>
RAPID SLOPE sensor for LEVEL PRO PLUS levelling system	<input type="checkbox"/>	<input type="checkbox"/>
Milling depth measurement and display in the LEVEL PRO PLUS display	<input type="checkbox"/>	<input type="checkbox"/>
Job data acquisition in the control display	<input type="checkbox"/>	<input type="checkbox"/>

- ☒ = Standard equipment  
☐ = Standard equipment, replaceable with optional equipment  
☐ = Optional equipment

	W 150 CF	W 150 CFi
<b>Operator's stand</b>		
Comfort operator's seat including seat heating	<input type="checkbox"/>	<input type="checkbox"/>
Operator's stand with weather canopy and lateral weather protection elements	<input type="checkbox"/>	<input type="checkbox"/>
Additional control unit for ground operation of the machine on the left	<input type="checkbox"/>	<input type="checkbox"/>
Heating operator's stand	<input type="checkbox"/>	<input type="checkbox"/>
<b>Others</b>		
Paint in one special colour (RAL)	<input type="checkbox"/>	<input type="checkbox"/>
Paint in two special colours (RAL)	<input type="checkbox"/>	<input type="checkbox"/>
Paint in maximum two special colours with substructure in special colour (RAL)	<input type="checkbox"/>	<input type="checkbox"/>
High-performance LED lighting package including rotating beacon.	<input type="checkbox"/>	<input type="checkbox"/>
Expanded electro-hydraulic unit	<input type="checkbox"/>	<input type="checkbox"/>
Additional weight 900 kg	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum assembly trolley to FB1500	<input type="checkbox"/>	<input type="checkbox"/>
Electric preheating of the fuel filter	—	<input type="checkbox"/>
Signal lights truck stop-and-go, folding	<input type="checkbox"/>	<input type="checkbox"/>
Powerful alternator for LED lighting balloons	<input type="checkbox"/>	<input type="checkbox"/>
Hydraulically driven water filler pump	<input type="checkbox"/>	<input type="checkbox"/>
High-pressure water cleaner, 150 bar 15 l/min	<input type="checkbox"/>	<input type="checkbox"/>
Milling drum rotation device	<input type="checkbox"/>	<input type="checkbox"/>
Pneumatic hammer with pick ejector/insertor	<input type="checkbox"/>	<input type="checkbox"/>
Hydraulically driven pick ejector drift	<input type="checkbox"/>	<input type="checkbox"/>
Additional folding seat for pick change with storage compartment	<input type="checkbox"/>	<input type="checkbox"/>
Diesel tank filling pump with 5.00 m suction hose	<input type="checkbox"/>	<input type="checkbox"/>
WITOS FleetView telematics system incl. 3-year operating period (EU)	—	<input type="checkbox"/>
WITOS FleetView telematics system incl. 3-year operating period (USA)	—	<input type="checkbox"/>
WITOS FleetView telematics system incl. 3-year operating period - PROMOTION	—	<input type="checkbox"/>
Monitor system with 2 cameras and screen	<input type="checkbox"/>	<input type="checkbox"/>
Monitor system with 5 cameras and 2 screens	<input type="checkbox"/>	<input type="checkbox"/>
LED illumination balloon, 24 volt	<input type="checkbox"/>	<input type="checkbox"/>
Large storage compartment on rear of machine	<input type="checkbox"/>	<input type="checkbox"/>

☒ = Standard equipment  
☐ = Standard equipment, replaceable with optional equipment  
☐ = Optional equipment



WIRTGEN GmbH

Reinhard-Wirtgen-Str. 2 · 53578 Windhagen · Germany

Phone: +49 (0)26 45/131-0 · Fax: +49 (0)26 45/131-392

Internet: [www.wirtgen.com](http://www.wirtgen.com) · E-Mail: [info@wirtgen.com](mailto:info@wirtgen.com)