



2020 • 2019 • 2018
EQUIPMENT DEALERS ASSOCIATION
SURVEY | TRACTOR MANUFACTURERS

**PRODUCT
QUALITY**

**YT235/
YT235C**

Comfort + Control + Innovation

INNOVATIVE DESIGN AND TECHNOLOGY



THIRD FUNCTION VALVE

control available and integrated into joystick



FACTORY CAB

with heat and air conditioning



ONE PIECE EASY OPEN STEEL HOOD



SKID STEER STYLE BUCKET ATTACHMENT

FEATURES

PERFORMANCE LINK
TECHNOLOGY™

ROPS PLATFORM OR
YANMAR-DESIGNED
FACTORY CAB WITH HEAT
AND AIR

ADVANCED CONTROLS
TO EASE OPERATOR
WORKLOAD & INCREASE
COMFORT

OPTIONAL YANMAR
DESIGNED LOADER

OPTIONAL, 60-INCH,
MID-MOUNT, FABRICATED,
DRIVE-OVER MOWER

OPTIONAL 7.5-FOOT
DIGGING DEPTH HYDRAULIC
BACKHOE

DUAL HYDRAULIC PUMPS

SMOOTH HYDRAULIC
POWER STEERING

TRUE 3-POINT HITCH
POSITION CONTROL

ONE-TOUCH-ON/OFF,
ELECTRO-HYDRAULIC,
INDEPENDENT PTO



| POWERTRAIN | YT235 ROPS | YT235 CAB |
|------------------------|-------------------------|-----------|
| Maker | Yanmar | |
| Model | 3TNV88C Tier4 | |
| Gross Power | 34.2 HP(26.1 kW)* | |
| PTO Power (@2,800 RPM) | 27 HP (20.1 kW) | |
| Rated RPM | 2,800 RPM | |
| Total displacement | 100.1 cu. In. (1.642 L) | |
| Aspiration | Naturally Aspirated | |
| Cooling system | Liquid cooled | |
| Number of cylinders | 3 | |
| Battery | 540 CCA | |
| Alternator | 40/55 | |
| Fuel tank | 7.4 gal. (28 L) | |

| DRIVETRAIN | |
|------------------------|--------------------------------|
| Transmission type | Hydrostatic (Dual Touch Pedal) |
| Rear differential lock | Foot pedal engagement |
| 2WD/4WD engagement | Selectable |
| Brake | Wet disc |
| Number of ranges | 3 |
| Rear PTO/RPM | 540 |
| Mid PTO/RPM | 2,013 |

| HYDRAULICS | |
|--------------------------------------|----------------------------------|
| Pump capacity (steering) | 4.1 GPM (15.5 L/min) @ 2,800 RPM |
| Pump capacity (implement) | 7.1 GPM (26.8 L/min) @ 2,800 RPM |
| 3-point hitch | Category 1 |
| 3-point lift capacity (std.) | 2,205 lbf. (1,000 kgf) |
| 3-point lift capacity at 24" (61 cm) | 1,764 lbf. (800 kgf) |
| 4-way loader control valve | Standard |
| Power steering | Fully Hydraulic |

| DIMENSIONS | | |
|--|-----------------------|-----------------------|
| Wheelbase | 65" (1,650 mm) | |
| Width (with R4 Tires) | 58.3" (1,482 mm) | |
| Overall length (with 3PH and R4 Tires) | 116.9" (2,970 mm) | |
| Overall height (with R4 Tires) | 89.0" (2,261 mm) | 83.6" (2,123 mm) |
| Ground clearance (with R4 Tires) | 10.8" (274 mm) | |
| Weight (with ROPS, R4 Tires, Full Fluid) | 2,558 lbs. (1,160 kg) | 2,910 lbs. (1,320 kg) |

| TIRE SIZE | | | | | |
|-----------|----|-------------|------|----|-------------|
| Front | R1 | 6" - 14" | Rear | R1 | 9.5" - 22" |
| | R3 | 9.5" - 22" | | R3 | 13.6" x 16" |
| | R4 | 13.6" x 16" | | R4 | 15" - 19.6" |

| TRAVELING SPEEDS | | |
|-------------------------|-----------------------------|--|
| Forward (with R4 Tires) | 0 - 11.7 mph (0 - 18.9 kmh) | |
| Reverse (with R4 Tires) | 0 - 8.2 mph (0 - 13.2 kmh) | |

*As rated by engine manufacturer

**Values published are for descriptive purposes only and Yanmar reserves the right to change the values.

†See your local Yanmar Independent Dealer for warranty coverage and any details.

Note: Attachments sold separately. Please see your local dealer for details.

| M60F MID-MOUNT MOWER | |
|----------------------|------------------------|
| Discharge type | Side Discharge |
| Mounting Method | Ground Following |
| Shell type | Fabricated 10 gauge |
| Cutting Width | 60" (1,524 mm) |
| Cutting Height | 1-4" (25.4 - 101.6 mm) |
| Weight | 283.8 lbs. (129 kg) |

| YL310 LOADER | |
|---|------------------------|
| Maximum lift height (to bucket pivot pin) | 84" (2,134 mm) |
| Reach with attachment on ground | 63" (1,600 mm) |
| Dump clearance | 60" (1,524 mm) |
| Digging depth at bucket level | 4.5" (114 mm) |
| Bucket width | 60" (1,524 mm) |
| Lift capacity at pivot pins | 1,300 lb. (590 kg) |
| Lift capacity at 500 mm forward of the pivot pins | 957 lb. (434 kg) |
| Breakout force 500 mm forward of the pivot pins | 1,549 lb. (703 kg) |
| Breakout force at pivot pins | 2,105 lb. (955 kg) |
| Raising time to full height w/o load | 2.6 sec. |
| Lowering time w/o load (power down) | 1.6 sec. |
| Bucket dumping time | 1.0 sec. |
| Bucket rollback time | 1.5 sec. |
| Bucket capacity | 8.48 cu. ft. (0.24 m³) |
| Grille guard | Standard |
| Tractor Length w/Loader | 12'8" (3861 mm) |
| Bucket Weight | 298 lb. (135 kg) |
| Loader Weight w/Bucket | 913 lb. (415 kg) |

| B75 BACKHOE | |
|--------------------------------------|------------------------|
| Digging depth (2' flat bottom) | 90" (2,286 mm) |
| Swing arc | 180° |
| Loading height (bucket at 60°) | 73" (1,854 mm) |
| Reach from centerline of swing pivot | 119" (3,022 mm) |
| Transport height (maximum) | 74" (1,879 mm) |
| Bucket rotation | 180° |
| Stabilizer spread - up position | 83" (2,108 mm) |
| Stabilizer spread - down position | 52" (1,320 mm) |
| Bucket cylinder digging force | 3,323 lbf. (1,507 kgf) |
| Dipperstick cylinder digging force | 2,192 lbf. (994 kgf) |
| Operating Pressure | 2,429 PSI (16.7 MPa) |
| Ramp angle (w/industrial tires) | 15° |
| Street pads | Option |
| Bucket options | Various (9" - 24") |
| Weight | 1,208 lb. (598 kg) |
| Tractor Length w/Backhoe & Loader | 18'6" (5,639 mm) |

| WARRANTY COVERAGE FOR YOUR TRACTOR† | |
|---|--------------------------|
| Tractor (Private Individual Usage) | 24 months or 2,000 hours |
| Powertrain(Engineandtransmissioncorecomponents) | 10 years or 3,000 hours |
| Attachments | 1-year limited warranty |