# 永州 翊 翔 和 电设备有限公司

YONG ZHOU YI XIANG MACHINERY&EQUIPMENT LTD.



yi≫iang 翊翔机电

# XT876 轮式挖掘装载机




#### 特点综述 FEATURES

**XT876轮式挖掘装载机**是双斗、前卸、整体、挖臂侧移、轮胎式挖装机可选用四合一铲斗、破碎锤和螺旋钻等多种机具,功能更加齐全。

**XT876 Backhoe Loader** is a kind of the multi-functional engineering machinery incorporating excavating and loading into an organic whole. The digging device can be pushed in the integral frame if necessary.

Various instruments such as four in one bucket, crash hammer and twist drill can be chosen.



## XT876 轮式挖掘装载机













#### 性能特点 SPECIFICATIONS AND CHARACTERS

①原装进口康明斯发动机,电控、电喷、高压共轨、空空中冷,节能环保,达欧III排放标准。箱、桥、液压系统等关键件均采用进口元件,提高了整机的可靠性。

Adopt the Cummins engine which is powerful and with low maintenance. Reach Europe III exhaustion standard. It has the high power and good performance ability ,The key parts such as the case, the bridge,the hydraulic system,etc.Adopt the imported components,which have improved the dependability of the complete machine.

②行驶速度高,提高了转场效率。转弯半径小,便于狭小空间作业。采用宽基工业轮胎、卓越的四轮驱动,获得强大的牵引力。

Traveling has been improved by means of the highest speed. It is usually used in the narrow ground because of the small turning radius. 4-wheel drive bring it high drawbar force.

③采用专用挖掘侧移整体式车架,提高了作业和行驶的稳定性。 Adopt the professional integral frame, which improves the operating stability.

④选用进口液压系统,提高了整机的作业能力。先进的操纵系统,控制精度更高。 With imported hydraulic system,the working ability has been improved. Advanced operating system, high control accuracy.

⑤结构合理的动臂缸支撑装置,使用方便,维修时安全可靠。

The supporting device of flexible-arm cylinder is well structured, Which makes it easier and safer to operate and maintain.

⑥ 湿式制动桥,制动平稳,保证行车安全。

Fully sealed wet multi-disc brakes in the wheel heads are protected from environmental influences.

⑦全采光封闭式驾驶室、符合ROPS标准,安全舒适,视野开阔。采用隔音、隔热、减震、冷暖空调系统的驾驶室,提高了操作环境的舒适性。

The whole day-lighting closed driver's cabin is furnished with the system of the air conditioner,ROPS system.It is safe and comfortable,and the visual field is broad.It adopts the sound insulation,the heat insulation and shock attenuation, which improved the comfortableness of the operating environment.

8新型可调仪表盘

It uses the new adjustable instrument panel.





# XT876 轮式挖掘装载机

XT870(挖掘中置式)/876 挖掘装载机主要参数		XT870 ( Backhoemiddle fixed )/876 Backhoe Loader		
项目 Description		XT870 参数 XT870 Specifications	XT876 参数 XT876 Specifications	单位 Unit
整机工作质量 Working weight		7300	8400	kg
外形尺寸(长×宽×高)Overall dimensions(L×W×H)		7173×2366×3437	5900×2300×3450	mm
最高车速(前进/后退)Max.travel speed		40.2/48.6	40.2/48.6	km/h
轴距 Wheel base		2152	2180	mm
转弯半径 Turning radius		4428	4428	mm
轮胎规格(前/后)Tires(F/R)		12-16.5/19.5L-24	14-17.5/19.5L-24	
工作油泵 Working oil pump	油泵型号 Oil pump model	KP30.15	KP30.15	
	额定转速 Max.travel speed	2200	2200	r/min
	额定压力 Rated pressure	21	21	Мра
发动机 Engine	额定功率 Rated power	74	82	kW
	额定转速 Rated speed	2200	2200	r/min
	型号 Model	B4.5T	QSB4.5	
	型式 Modality	增压、水冷、四缸、四冲程直列式	中冷电控高压共轨	VIC.
	总排气量 Overall displacement	4.5	4.5	L
	最低燃油消耗率 Fuel consumption	225	213	g/Kw.h
装载装置 Loading installment	铲斗容量 Bucket capacity(heaped)	0.8~1.2	0.8~1.2	m3
	最大卸载高度 Dumping clearance	2825	2825	mm
	最大卸载距离 Dumping reach	727	745	mm
	掘起力 Break-out force	42	42	KN
挖掘装置 Excavation installment -	挖斗容量 Digger capacity	0.25~0.35	0.20~0.35	m3
	最大挖掘深度 Max.digging depth	4495	4100	mm
	最大挖掘半径 Max.digging radium	5471	5400	mm

## \_yi∞iang

www.crane-china.com 幽翔机电

### yi ang 永州 強翔 机电设备有限公司

地址:湖南省长沙市五一大道韭菜园路389号华美欧大厦2013-2014室 ADD:ROOM 2013-2014, HUAMEIOU BUILDING, NO.389, WUYI AVE.CHANGSHA,HUNAN,CHINA

邮址(E-mail):info@crane-china.com 总机(TEL):86-731-85816117 82880555/666/777 传真(FAX):86-731-85816217 82880111

电话(TEL):86-746-8422780 8323288 传真(FAX):86-746-8420289 地址:湖南省永州市冷水滩区湘永路129号中亚家园2104室 ADD:ROOM 2104, ZHONGYA JIAYUAN, NO.129 XIANGYONG RD, LENG SHUI TAN DISTRICT, YONGZHOU, HUNAN, CHINA